

GUTMANN S80v+HW



HUG | Switzerland







ALUMINIUM
WINDOW SYSTEM

SYSTEM DESCRIPTION

Premium window in the 80 mm series with concealed sash and peak value of $U_f = 1.3 \text{ W/m}^2\text{K}$.

- › 5 chamber, coextruded hollow-chamber central gasket, glass rebate Insulation for improved thermal Insulation of the frame (HW = highly insulated).
- › Symmetrical, stable structural design with identical corner and T connectors.
- › Thermal and structural high-end insulators in GUTtherm material technology.
- › Glass bead made from reinforced PA 6.6.
- › Euro groove for free choice of hardware.
- › Surface mounted fittings up to sash weights of 300 kg; concealed fittings up to 180 kg.
- › Face width from 71 mm for tilt & turn windows .
- › Glass up to 56 mm in the sash, 55 mm in the fixed panel.
- › Soundproofing up to 47 dB (SSK 5).
- › Burglar resistance RC 1, RC 2 and RC 3 in accordance with DIN EN 1627.

SYSTEM PROPERTIES OF CLASSES

	Water tightness	E1050		Wind load	C5/B5
	Air permeability	4		Operating forces	1

PB 12-00 2023 ff

THERMAL INSULATION



¹ Element size: 1,230 x 1,480 mm | U_g value: 0.6 $\text{W/m}^2\text{K}$ | Glass spacer: Swisspacer Ultimate

SYSTEM CROSS SECTION

